

STORAGE TANK LEAK DETECTION INSTALLATION OR UPGRADE APPLICATION / NOTIFICATION

Environmental & Regulatory Services Division Bureau of Petroleum Products and Tanks P.O. Box 7837 Madison, WI 53707-7837 (608) 267-9795 (608) 266-8981

INSTRUCTIONS: This form is to be submitted to the Department of Commerce along with the plan submittal for new installations, or submitted independently for conversions of existing systems from one leak detection methodology to another or upgrade of existing methods, equipment or software along with the respective startup tests (ATG) or precision test (SIR). For existing equipment, submit this form within five days of installation to the Department of Commerce at the address in the upper right corner of this page. Refer to Comm Table 2.43 for fee submittal.

Personal information you provide may be used for secondary purposes [Privacy Law, s. 15.04(1)(m)].

	<u></u>	<u></u>	□Copy to F	•			
I certify by signature that provisions of the curre 40 CFR Part 280, manufacturer's instructions a		□Plan Review □Copy to Inspector					
Addition OR Upgrade for leak detection \$ (7636) \$ (8253) \$			For Office Use Only Transaction #				
FEES: (Fee table on reverse side) Plan Re	•	Total	Fan Office III	aa Omb			
Comments:							
Total length of pipe:	: :	:	: :	: :			
Line size (diameter):		:	: :	: :			
Indicate by (N) No, (UD) Under Dispenser, (TT) Tall Are sump sensors installed?		:	<u> </u>				
Does the manifold line include a check valve to isola	ate the line?	; ; ;					
Is line manifolded to another line? Indicate reg obj r		:					
Leak detection method: Electronic line moni			Tightnes	s testing			
System Type: ☐ Pressurized piping with → A. ☐ auto shutoff; B. ☐ alarm or C. ☐ flow restrictor ☐ Suction piping with check valve at tank ☐ Suction piping with check valve at pump and inspectable							
Configuration: Single wall Double wall	Type: Steel Fiberglas		Other (Specify):				
	DETECTION UPGRADE ONLY						
Does the manifold line include an isolation valve to isolate the line? IndicateY/N							
Is tank manifolded to another tank? Indicate reg obj number of the other tank.				: :			
Monthly estimated throughput for Continuous ATG or SIR systems:							
Console Name Designation/ Model Number:							
Minimum product level for test - Indicate %, inches or gallons:							
Probe Model Numbers:		:	: :				
Probe Type: (U) ultrasonic, (M) magnetostrictive, (C) capacitance							
Interstitial Monitoring (Y) Yes (NA) Not Applicable							
Product:		:	: :	: :			
Tank size:		•		- · · · · · · · · · · · · · · · · · · ·			
Reg. Obj #:		:	· :	:			
Tank leak detection method: ☐ Automatic tank gauging ☐ Continuous ATG ☐ Inventory control and tightness testing ☐ Interstitial monitoring ☐ Statistical Inventory Reconciliation (SIR) [Review fee, but no system inspection fee]							
TANK INFORMATION TANK MONITOR UPGRADE ONLY Tank leak detection method: Automatic tank gauging Continuous ATG Inventory control and tightness testing Interstitial monitoring							
<u> </u>	OR LIBGRADE ONLY						
Leak Detection Equipment Manufacturer: Software Version, if applicable:		VVIIV	Material Approval No. :				
TANK SPECIFICATIONS: Underground Aboveground							
	: Date projected to be installed:	LJ Post In:	stallation: Date Installed:	-			
THIS FORM IS SUPMITTED. The second of	,	()	()			
Telephone Number Fax Number	Fire Dept. Providing Fire Coverage	FDID# Telepho	Telephone Number Fax Number				
City, State, Zip Code	County	Contac	Contact Person Customer ID#				
Number and Street	☐ City ☐ Village ☐ Town o	of: City, St	City, State, Zip Code				
Company Name	Site Address	Numbe	Number and Street				
Name	Facility Name Contractor Name						
Customer ID#	Site ID# Facility ID#	mer ID#					
OWNER INFORMATION	PROJECT INFORMATION	CONTE	RACTOR INFORMATION				

STORAGE TANK LEAK DETECTION INSTALLATION OR UPGRADE APPLICATION / NOTIFICATION

Completing this form:

This form is to be completed when installing a new method of leak detection or when modifying or upgrading the existing leak detection methodology or equipment. This form is to be submitted to the Department of Commerce along with the plan submittal for new installations, or submitted independently for conversions of existing systems. For leak detection modification to existing equipment, submit this form within <u>five days</u> of installation to the <u>Department of Commerce</u> at the address in the upper right corner of the first page.

This form is designed to provide the pertinent information relating to ATG, Interstitial and SIR tank leak detection methodologies, as well as the various product pipe leak detection methodologies. The fill-in blanks and questions will not always apply to a specific methodology and can be left blank or marked NA. The following items are provided as a guide to completing this form:

- ♦ Leak Detection Equipment Manufacturer section will apply to any equipment or SIR vendor.
- Software version section will apply to any electronic monitoring or SIR related software that is installed on a PC or control device at the facility.
- Tank leak detection method is the method that the system is implementing
- ♦ Probe Type & Probe Model Number sections apply to ATG and SIR when the inventory data is via a probe rather than a stick reading.
- Minimum product level for test section is the threshold that the methodology vendor and respective material approval designate. The option is gallons, percentage or inches, but should correlate with the reading that is printed on a tape.
- ♦ Monthly estimated throughput for CSLD or SIR systems section is a figure that the owner/operator will furnish. The operator should have a projection for new systems.
- "Is line manifolded" in the Pipe Information section needs to be completed only if a tank line is manifolded to another tank line. The entry must be the regulated object number of the other tank.
- When using a check valve in the manifolded line or a submersible pressure relief, provide the set point pressure of the relief valve.
- Total length of pipe section is the length of pipe associated with each line leak detector

This form is designed for the typical configurations and application of leak detection methodologies. It is likely that unique or non-typical system configurations will be experienced. Remarks in the "Comment" section would be appropriate.

This form must be signed by the technician or person responsible for performing the equipment installation or assessing the facility attributes to implement the transition from one leak detection methodology or one vintage of an existing methodology to another.

Submittal Fee:

Upgrade, exchange or conversion of existing leak detection methodology to another approved methodology or manufacturer.

	Plan Review	Installation Inspection	Plan Revision Fee	Re- inspection
	Fee	Fee \$100		Fee
When submitted independent of a broader plan submittal application	\$35	Except conversion to SIR	\$100	\$100